

# 5500528

tarmac rally - race

Renault Alpine A110, R12 Gordini

I-4cyl 1.6L 8v OHV (FT/FT)



**intake**                      **exhaust**

**camshaft data:**


lash ramp	: 0.40mm	0.40mm
duration @ 0.1mm	: 300°	300°
duration @ 1.0mm	: 258°	258°
valve lift	: 11.15mm	11.15mm
cam lift	: 7.00mm	7.00mm
lobe angle	: 106°	106°
timing @ 1.0mm	: 23° / 55°	55° / 23°
valve lift @ TDC	: 3.95mm	4.00mm

**parts setup:**

cam wheels :	:	:
follower	: O.E.M.	: O.E.M.
valve lash	: O.E.M.	: O.E.M.
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: O.E.M.	: O.E.M.
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: O.E.M.	: O.E.M.
interior spring	: O.E.M.	: O.E.M.

fitted load / length	: 40kg @ 39.5mm	: 40kg @ 39.5mm
max. load / lift	: 78kg @ 11.5mm	: 78kg @ 11.5mm

**REMARKS :**



**REMARKS :**

- # - cam lobe sequence: **II-II-II-II** (crossflow head)
- total length: **519mm**
- journal diameters: 41.94 - 41.94 - 41.94 - 34.94mm - 31.94mm
- pump between cam lobe 2-3 (version with pump between cam lobe 7-8 is not available)
- available in steel billet only
  
- # ONLY for dirt track applications and pro street use with adjustable engine management or carburetors